



1949 - 1954 Chevy Passenger Car Rear Leaf Spring Installation Instructions

1-855-693-1259

www.totalcostinvolved.com

Read and understand these instructions before starting any work!
CHECK ALL PARTS INCLUDED IN THIS KIT TO THE PARTS LIST BEFORE INSTALLATION.
IF ANY PIECES ARE MISSING, PLEASE CONTACT: TOTAL COST INVOLVED 855-693-1259

Note:

These instructions are for the replacement of the existing factory rear leaf spring suspension. Read through all of the instructions before beginning the installation.

Place the vehicle on a hard level surface & use an appropriate jack & jack stands to raise the vehicle off the ground.

Remove the rear wheel, rear axle assembly, and the existing rear leaf spring suspension.

Remove the rivets from the front and rear leaf spring hanger brackets on the frame. Use a grinder to grind down the heads of the rivets, then use a hammer and chisel to tap them out.

Figure 1



Install the new front leaf spring hangers. (*Note: There is a left and right front hanger.) Match the holes in the brackets to the rivet holes in the frame. Three of the holes will line up and you will need to drill the fourth hole. When the brackets are placed correctly, the tabs to hold the spring should be to the rear of the vehicle. (See **Figure 1**)


Figure 2



Install the new rear leaf spring hangers. Line up the rear holes in the bracket with the rivet holes in the frame. You will need to drill the 2 additional holes for the front of the bracket. (See **Figure 2**)

Figure 3

Install the new leaf springs. The leaf spring should be positioned with the pressed-in bushing in the front hangers (toward the front of the vehicle). The empty spring eye will take the shackle bushing and attach to the rear hangers with the shackles. (See **Figure 3**)

Figure 4


Set the spring perches on the centering pins on the leaf springs. Then set the rear axle assembly housing in place, centering the housing from side to side accounting for wheel position in the fender wells. Check the pinion angle. The pinion angle should be 3 degrees up. Adjust the pinion angle and side-to-side position of the rear axle assembly until it is properly aligned. When the rear axle assembly is properly aligned tack weld the axle pads to the rear axle assembly housing. *Note: Leaf spring pads are center to center at 43" (See **Figure 4**)

Install the U-bolt and 5-hole plates positioned so that the shock mounting tabs are to the front of the axle assembly housing and toward the center of the vehicle. Tighten all nuts on the U-bolts. (We recommend a torque of 60 lbs. /ft.)

Figure 5

Next install the shocks in the stock upper location. Then install the special lower shock mount bolt into the tab on the U-bolt 5-hole plate. Now bolt the lower shock eye onto the lower shock mount. (See **Figure5**)

Parts List



**Thank you for purchasing a TCI Product. If you have any questions please call
1-855-693-1259
or visit www.totalcostinvolved.com.**